

### PRODUCT INFORMATION SHEET



**CAPT-AIR®**

8001 Rue Larrey, Anjou, QC, Canada, H1J 2L4  
514-273-4331 • info@capt-air.com • www.capt-air.com

#### Description

The IEP Technologies range of passive isolation flap valves are low cost and reliable explosion isolation solutions which mitigate explosion propagation risks to upstream equipment. These passive isolation solutions are effective, self-actuating devices providing inlet explosion isolation to protected vessels handling combustible dusts such as dust collectors, cyclones, and other process equipment.

Available models include the IsoFlap® and IsoFlap®-M passive isolation valve. The IsoFlap version is 3rd party certified as a protective system according to EU directive 2014/34/EU (ATEX Directive) and is approved for isolation of dust explosions. The IsoFlap-M has integrated monitoring of dust accumulation level in the valve body and the blade position which meets the requirements of OSHA Combustible Dust Directive, NFPA 654, and NFPA 69.

The IsoFlap and IsoFlap-M both have a durable carbon steel valve body, or an optional all stainless-steel body construction, and a flap blade. The valve is designed to withstand high maximum reduced explosion pressures (Pred) listed in the specification section below. During operation the flap blade is held open by the process airflow, in case of an explosion the pressure front closes and locks the blade in place, mitigating the propagation of the flame and pressure to the upstream equipment.

Available as an option is the IsoFlap-M Interface Module, a PCB based system monitoring device designed for use with the IsoFlap-M version of the flap valve. The Interface Module includes intrinsically safe barriers for monitoring the IsoFlap-M sensors, provides for process interlock functions, and includes diagnostic and maintenance functions. The Interface Panel operates on either 120 or 230 VAC.

#### Features

- Certified according EN16447
- IsoFlap-M monitored version fully compliant to NFPA 69 with continuous dust accumulation and flap position monitoring
- Low pressure drop
- Short mounting distances
- Tested and approved to allow up to two elbows between IsoFlap and downstream vessel
- Easy access through hinged inspection cover with gas spring assisted cover opening for valves  $\geq$ DN630
- Passive design without triggering sensors
- Leak tight design with bearing shaft internal to housing
- Cylindrical housing design reduces product build-up
- Corrosion resistant design confirmed by salt spray corrosion test
- Suitable for PUSH / PULL applications
- Approved for metal dust applications

#### IsoFlap®



#### IsoFlap-M Interface Module



## Application

Wherever a passive explosion isolation device is suitable, the IEP Technologies flap valve series IsoFlap offer a very cost effective solution to mitigate the risk of explosion propagation to connected equipment.

When applying explosion protection methods such as venting or flameless venting it is also necessary to reduce the risk of explosion propagation between interconnected process vessels. Here the IsoFlap valves offer an effective, self actuating explosion isolation to protected vessel handling combustible dusts.

Typical applications for the IEP Technologies IsoFlap valve include inlet explosion isolation of dust collectors, cyclones and other process equipment.

## Specifications

Nominal Diameter mm(in)	K <sub>st</sub> max. bar m/sec	Minimum Vessel Volume m <sup>3</sup> (ft <sup>3</sup> )	PRED max. bar (psi)	Minimum Mounting Distance with 0 or 1 Elbow m (ft)	Minimum Mounting Distance with 2 Elbows m (ft)	Maximum Mounting Distance m (ft)	Pressure Drop @ 20 m/s or 3950 ft/min Pa (in-H <sub>2</sub> O)			
100 (4)	300 (ST1 & ST2)	0.46 (16.2)	1.0 (14.5)	1.5 (5.0)	2.6 (8.5)	7.0 (23)	200 (0.804)			
150 (6)			1.0 (14.5) for ST1 0.5 (7.25) for ST2	2.0 (6.6) for ST1 2.5 (8.2) for ST2	3.1 (10.2) ST1 Only		190 (0.764)			
200 (8)					3.2 (10.5) ST1 Only		220 (0.884)			
250 (10)	200 (ST1)	1.7(60.0)	0.5 (7.25)	3.5 (11.5)	4.7 (15.4)	8.0 (26.2)	260 (1.045)			
315 (12)										280 (1.125)
355 (14)										300 (1.206)
400 (16)		1.6 (56.5)	0.45 (6.5)	5.0 (16.4)	6.4 (21.0)		240 (0.964)			
450 (18)										260 (1.045)
500 (20)										280 (1.125)
560 (22)	6.0 (212.0)	0.35 (5.0)	5.6 (18.4)	6.1 (20.0)	8.5 (27.9)	310 (1.246)				
630 (25)									330 (1.326)	
710 (28)									350 (1.407)	
800 (32)									490 (1.969)	
900 (36)						520 (2.090)				
1000 (40)						550 (2.210)				

Metal dust ST1 (DN100 to DN355)  
 PUSH ST1 (DN100 to DN500)  
 PULL (all sizes)  
**Note - table not be used for design / Please contact IEP Technologies for assistance.**

## Contact Information

IEP Technologies - Austria  
 (HOERBIGER Safety Solutions)  
 Tel: +43 1 2244 0

IEP Technologies - Belgium  
 (HOERBIGER Safety Solutions)  
 Tel: +49 2102 5889 0

IEP Technologies - Finland  
 Tel: +358 10 325 358 0

IEP Technologies - France  
 Tel: +33 1 5803 3980

IEP Technologies - Germany  
 Tel: +49 2102 5889 0

IEP Technologies - Italy  
 (HOERBIGER Safety Solutions)  
 Tel: +39 045 2370762

IEP Technologies - Sweden  
 (HOERBIGER Safety Solutions)  
 Tel: +46 70 564 3306

IEP Technologies - Switzerland  
 Tel: +41 62 207 10 10

IEP Technologies - Turkey  
 Tel: +90 232 484 4412

IEP Technologies - UK  
 Tel: +44 1242 283 060

IEP Technologies - USA  
 Tel: +1-855-793-8407

IEP Technologies - Latin America  
 (HOERBIGER Safety Solutions)  
 Tel: +55 (11) 4446 7400

IEP Technologies - China  
 (HOERBIGER Safety Solutions)  
 Tel: +86 21 6485 0855 Ext 8211

IEP Technologies - South East Asia  
 (HOERBIGER Safety Solutions)  
 Tel: +65 6890 0770