

T Series

# T Series Industrial Vacuums

- three-phase, electric vacuums for every application



# Tailor-Made Cleaning Solutions

- specific features for all industry application needs

The T Series offers continuous-duty industrial vacuum cleaners with strong performance at an affordable price. Ideal for collection of powders, liquids, dust and debris, the vacuums are easy to use and maintain, even in the most challenging environments.

## Features and Benefits

The T26, T48 and T63 are equipped with motors from 2,600 up to 6,300 W, allowing users to choose the most suitable model for their needs. With the following features, the T Series makes daily cleaning in production areas and process manufacturing fast and hassle-free:

- Constructed of heavy duty steel and polypropylene
- Lightweight and highly maneuverable with rear swiveling wheels and locking brakes
- Unique release lever lowers the wheeled collection container and acts as a handle for fast and easy disposal of collected debris
- Compatible with a wide range of Nilfisk attachments and hoses to meet specific application requirements
- Low noise operation, increasing worker safety and comfort



## Upgrade to the T-Plus series for optional:

- electrical upgrades
- automatic filter cleaning
- wet or dry sensors
- remote start/stop

## Technical Specifications

Description	Unit	T26	T48	T63
Type of Power	-	Dry (Wet Option)	Dry (Wet Option)	Dry (Wet Option)
Collection Type	-	3-Phase	3-Phase	3-Phase
Voltage @ 60 Hz	V	220 / 460 / 575	220 / 460 / 575	220 / 460 / 575
Power @ 60 Hz	HP (W)	3.42 (2550)	6.43 (4800) [6.17 (4600) @ 575]	8.45 (6300)
Waterlift, controlled	in. (mm) H <sub>2</sub> O	76 (1930)	140.5 (3569)	82.6 (2100)
Airflow, blower max.	CFM (L/min)	222 (6286)	222 (6286)	345 (9769)
Current, max.	amps	11.4 / 6 / 4.55	25 / 10.4 / 7.6	25 / 13.3 / 10.4
Container Capacity	gallons (L)	26 (100)	222 (6286)	222 (6286)
Main Filter Area (Standard)	ft <sup>2</sup> (m <sup>2</sup> )	20.99 (1.95)	20.99 (1.95)	20.99 (1.95)
Main Filter Area (Oversized)	ft <sup>2</sup> (m <sup>2</sup> )	31.22 (2.9)	31.22 (2.9)	31.22 (2.9)
HEPA Filter Area, upstream	ft <sup>2</sup> (m <sup>2</sup> )	37.7 (3.5)	37.7 (3.5)	37.7 (3.5)
Machine Inlet Diameter	mm	70	70	70
Dimensions (L x W x H)	in. (mm)	44.5 x 23.6 x 60.2 (1130 x 600 x 1530)	44.5 x 23.6 x 60.2 (1130 x 600 x 1530)	44.5 x 23.6 x 60.2 (1130 x 600 x 1530)
Weight	lb. (kg)	251.3 (114)	297.6 (135)	306.4 (139)
Cord Length	ft. (m)	30 (9)	30 (9)	30 (9)
Protection Class	-	IP55	IP55	IP55
Sound Pressure Level	dB(A)	71	74	74

Specifications subject to change without notice. The data, characteristics, colors and illustrations are merely indicative and therefore not binding.



# Endless Possibilities

- for industry specific applications



## Technical Specifications

Description	Unit	T26 PLUS	T48 PLUS	T63 PLUS
Type of Power	-	Dry (Wet Option)	Dry (Wet Option)	Dry (Wet Option)
Collection Type	-	3-Phase	3-Phase	3-Phase
Voltage @ 60 Hz	V	220 / 460 / 575	220 / 460 / 575	220 / 460 / 575
Power @ 60 Hz	HP (W)	3.42 (2550)	6.43 (4800) [6.17 (4600) @ 575]	8.45 (6300)
Waterlift, controlled	in. (mm) H <sub>2</sub> O	76 (1930)	140.5 (3569)	82.6 (2100)
Airflow, blower max.	CFM (L/min)	222 (6286)	222 (6286)	345 (9769)
Current, max.	amps	11.4 / 6 / 4.55	25 / 10.4 / 7.6	25 / 13.3 / 10.4
Container Capacity	gallons (L)	26 (100)	26 (100)	26 (100)
Main Filter Area (Standard)	ft <sup>2</sup> (m <sup>2</sup> )	20.99 (1.95)	20.99 (1.95)	37.7 (3.5)
Main Filter Area (Oversized)	ft <sup>2</sup> (m <sup>2</sup> )	31.22 (2.9)	31.22 (2.9)	-
HEPA Filter Area, upstream	ft <sup>2</sup> (m <sup>2</sup> )	37.7 (3.5)	37.7 (3.5)	37.7 (3.5)
ULPA Filter Area, downstream	ft <sup>2</sup> (m <sup>2</sup> )	86.11 (8.0)	86.11 (8.0)	86.11 (8.0)
Machine Inlet Diameter	mm	70	70	70
Dimensions (L x W x H)	in. (mm)	50.8 x 23.6 x 60.6 (1290 x 600 x 1540)	50.8 x 23.6 x 60.6 (1290 x 600 x 1540)	50.8 x 23.6 x 60.6 (1290 x 600 x 1540)
Weight (w/o cartridge)	lb. (kg)	303 (137)	356 (161)	367 (166)
Cord Length	ft. (m)	30 (9)	30 (9)	30 (9)
Protection Class	-	IP55	IP55	IP55
Sound Pressure Level	dB(A)	67	71	71

Specifications subject to change without notice. The data, characteristics, colors and illustrations are merely indicative and therefore not binding.

## Safe Choice Commitment

At Nilfisk Industrial Vacuums we understand that you face many risks each day, just by operating your business. That is why Nilfisk is dedicated to helping you make smart choices to keep your facility and your workers safe. Our team of experts is ready to tackle any cleaning challenge – because in a world full of risk, you have to make safe choices.

We are committed to being that safe choice. To learn more visit [nilfiskindustrialvacuums.com](http://nilfiskindustrialvacuums.com).

