

PistonFire II

HIGH RATE DISCHARGE SUPPRESSOR

PRODUCT INFORMATION SHEET



CAPT-AIR®

8001 Rue Larrey, Anjou, QC, Canada, H1J 2L4
514-273-4331 • info@capt-air.com • www.capt-air.com

Description

The IEP Technologies PistonFire II Suppressor consists of a pressurized suppressant storage cylinder and a valve body that contains a dust-ignition proof, weatherproof NEMA enclosure. The NEMA enclosure houses the actuating mechanism, pressure switch, pressure gauge, fill valve, OSHA supervisory switch, and field wiring connections. The NEMA enclosure is completely sealed to ambient via screw cover and an explosion proof quick-disconnect connector for easy connection to field wiring. The OSHA supervisory switch prevents the arming of the explosion protection system when the OSHA lockout plate is installed. The OSHA lockout plate can be secured in place to the designated location on the PistonFire II housing. The pressure switch provides a trouble signal to the control panel if the suppressor pressure drops out of its proper operating pressure. Upon detection of an incipient explosion, the suppressor is sent an actuation signal. The actuating mechanism initiates the rapid release of the pressurized, suppressant into the protected area within milliseconds.

Advantages

- Non-explosive operation increases safety, and reduces storage, licensing, and transportation concerns.
- Up to five year initiator service life reduces maintenance costs.
- DOT approved, the suppressor is shipped fully pressurized, reducing installation time and cost.
- Meets new stringent requirements of NFPA 69.
- Corrosion resistant valve body
- Supervised, integral OSHA lockout/tag-out provision promotes safe entry into protected vessels.
- Supervisory low pressure switch continuously monitors suppressor nitrogen pressure.
- Innovative field-rechargeable design reduces service time, recharge costs and production downtime.
- Designed for use in hazardous locations; Class II, Div. I.

Application

The IEP Technologies PistonFire II Suppressor is designed to discharge suppressant in milliseconds within a process vessel or to mitigate the propagation of flame through interconnected ductwork. It is used in conjunction with IEP Technologies' range of control panels and detectors.

IEP Technologies sophisticated computer modeling techniques determine the quantity and size of suppressors to be used. These techniques predict reduced explosion pressures based on actual process conditions and detector settings.

PistonFire II




Specifications

Construction:	Valve body: corrosion resistant materials including stainless steel and aluminum. Spun cylinder: painted carbon steel (red). Operating Plate: painted carbon steel (red).
Actuation:	Non-explosive PF Initiator included with suppressor.
Approvals:	ATEX and FM approved.

Dimensions

Model	A (in.)	B (in.)	C (in.)
PFII-1000	12.0	23.5	5.5
PFII-2000	12.0	30.1	8.0
PFII-3000	12.0	40.8	9.0



Ordering Information

Part Number	Description	Weight (lbs.)
32-500005-001	PFII-1000 PistonFire Suppressor, Class II, Div. I (8.8 lbs. of agent)	77
32-500006-001	PFII-2000 PistonFire Suppressor, Class II, Div. I (23.8 lbs. of agent)	118
32-500007-001	PFII-3000 PistonFire Suppressor, Class II, Div. I (47.6 lbs. of agent)	168
32-500015-001	PFII-1000 PistonFire Suppressor, Class I, Div. II (8.8 lbs. of agent)	77
32-500016-001	PFII-2000 PistonFire Suppressor, Class I, Div. II (23.8 lbs. of agent)	118
32-500017-001	PFII-3000 PistonFire Suppressor, Class I, Div. II (47.6 lbs. of agent)	168
06-237129-001	PistonFire Lifting Strap	2
32-094053-020	PistonFire II Reconditioning Kit with Pressure Switch (Class II, Div. I)	5
32-094053-023	PistonFire II Reconditioning Kit with Pressure Switch (Class I, Div. II)	5
32-094053-022	PistonFire II Depressurization Kit (Class II and Class I)	3
32-193023-001	Cable Kit (Class II, Div I)	2
32-099932-030	PistonFire II initiator (Class II and Class I)	<1

Contact Information

IEP Technologies - Austria
(HOERBIGER Safety Solutions)
Tel: +43 1 2244 0

IEP Technologies - Belgium
(HOERBIGER Safety Solutions)
Tel: +49 2102 5889 0

IEP Technologies - Finland
Tel: +358 10 325 358 0

IEP Technologies - France
Tel: +33 1 5803 3980

IEP Technologies - Germany
Tel: +49 2102 5889 0

IEP Technologies - Italy
(HOERBIGER Safety Solutions)
Tel: +39 045 2370762

IEP Technologies - Sweden
(HOERBIGER Safety Solutions)
Tel: +46 70 564 3306

IEP Technologies - Switzerland
Tel: +41 62 207 10 10

IEP Technologies - Turkey
Tel: +90 232 484 4412

IEP Technologies - UK
Tel: +44 1242 283 060

IEP Technologies - USA
Tel: +1-855-793-8407

IEP Technologies - Latin America
(HOERBIGER Safety Solutions)
Tel: +55 (11) 4446 7400

IEP Technologies - China
(HOERBIGER Safety Solutions)
Tel: +86 21 6485 0855 Ext 8211

IEP Technologies - South East Asia
(HOERBIGER Safety Solutions)
Tel: +65 6890 0770